



Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 0,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection.

Integral EC electronic converter.


Luminaire requires installation blockout and sealable junction box, which are included in supply.


2700 K option available on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

Weight	6.30 kg	
Light distribution	symmetric, diffused distribution	
Light source	LED-6/12W / 700 mA - 3000 K	
CRI	80	
Power supply	EC	
LEDs	6	
Rated input power	14.5 W	
Nominal Lumen (lm)		
LED Lumen	290	
Total Lumen	1740	
Tj	85	
Rated lumens (lm)		
LED Lumen	61.5	
Total Lumen	369.2	
Та	25	







Specifications Material description

Body Stainless steel construction

Lens Safety glass lens with opal diffuser, max. load 5 tonnes

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.

WE-EF LIGHTING Pty Ltd





Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0325	250

