



Description

IP67, Class I. IK07. Stainless steel inground section. Diecast hood made from marine-grade aluminium alloy. Construction helps to prevent accumulation of insects, leaves and debris on lens and restricts glare to passersby. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone rubber gasket. Factory-sealed termination chamber with cable gland and 0.5 m of flexible PVC-free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. Luminaire installation blockout and sealable junction box included in supply.


2700 K option available on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

Weight	14.80 kg	
Light distribution	symmetric, medium beam [M]	
Light source	LED-12/24W / 700 mA - 4000 K	
CRI	80	
Power supply	EC	
LEDs	12	
Rated input power	27 W	
Nominal Lumen (lm)		
LED Lumen	310	
Total Lumen	3720	
Tj	85	
Rated lumens (Im)		
LED Lumen	210.9	
Total Lumen	2530.6	
Та	25	







Specifications Material description

Body Stainless steel inground section. Die-cast hood made from marine-grade aluminium alloy

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK07

Corrosion resistance 5CE. 5CE+Primer optional

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

Additional information

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details.

Warranty void if installed without proper drainage!





Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0325	250

