ESC330-FS LED





Description

IP67. IK07. Stainless steel inground section. Die-cast hood made from marine-grade aluminium alloy. Construction helps to prevent accumulation of insects, leaves and debris on lens and restricts glare to passers-by. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone rubber gasket. Factory-sealed termination chamber with cable gland and 0.5 m of flexible PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.


Luminaire installation blockout and sealable junction box included in supply.


Weight	14.80 kg	
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]	
Light source	LED-12/24W / 700 mA - 4000 K	
CRI	80	
Power supply	EC	
LEDs	12	
Rated input power	27 W	
Nominal Lumen (lm)		
LED Lumen	310	
Total Lumen	3720	
Tj	85	
Rated lumens (lm)		
LED Lumen	227.6	
Total Lumen	2731.3	
Та	25	

185-7495

ESC330-FS LED







Specifications Material description

Body Stainless steel inground section. Die-cast hood made from marine-grade aluminium alloy

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone rubber gasket

Fasteners PCS hardware

Ingress protection IP67
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Driver / Ballast Integral EC electronic converter

Additional information

185-7495

ESC330-FS LED



Control

DALI interface

Description	Part ID
DALI interface	430-0013

1-10 V analogue dimming interface

Description	Part ID
1-10 V analogue dimming interface	430-0011

185-7495

ESC330-FS LED



Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0325	250

