



Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD-optimised optics for superior illumination and glare control.

Luminaire requires installation blockout and sealable junction box, which are included in supply.


2700 K option available on request.


ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

Weight	6.40 kg
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]
Light source	LED-12/24W / 700 mA - 3000 K
CRI	80
Power supply	EC
LEDs	12
Rated input power	27 W
Nominal Lumen (lm)	
LED Lumen	290
Total Lumen	3480
Tj	85
Rated lumens (lm)	
LED Lumen	252.8
Total Lumen	3033.1
Та	25







Specifications Material description

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

Additional information

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.

WE-EF LIGHTING Pty Ltd





Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0325	250





Optical Accessories

Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7170	191



Surface wash lens

Description	Part ID	C1
Flood lens IO-360	185-7171	191





ETC330-FS LED

Colour filter

Description	Part ID	
Colour filter IF	on request	



Wallwash lens

Description	C1
IO-20-WW-ETC/EVC_30-FS-LED	191

