ETC340-FS LED





Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD-optimised optics for superior illumination and glare control.

Luminaire requires installation blockout and sealable junction box, which are included in supply.

2700 K option available on request.


ASC Anti Slip Coating on request.


IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

Weight	11.00 kg	
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]	
Light source	LED-24/36W / 500 mA - 3000 K	
CRI	80	
Power supply	EC	
LEDs	24	
Rated input power	39 W	
Nominal Lumen (Im)		
LED Lumen	215	
Total Lumen	5160	
Tj	85	
Rated lumens (lm)		
LED Lumen	200.8	
Total Lumen	4818.2	
Та	25	

ETC340-FS LED







Specifications Material description

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.

ETC340-FS LED



Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300




ETC340-FS LED



Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19




ETC340-FS LED



Optical Accessories

Surface wash lens

Description	Part ID	C1
Flood lens IO-360	185-7579	220



Linear spread lens

Description	D C1
inear spread lens IO-180	7580 220







Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	185-7589	220

