



Description

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blockout and sealable junction box included in supply.


ASC Anti Slip Coating on request.


IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

Weight	12.00 kg
Light distribution	symmetric, wide beam [B]
Light source	LED-12/24W / 700 mA - 3000 K
CRI	80
Power supply	EC
LEDs	12
Rated input power	27 W
Nominal Lumen (lm)	
LED Lumen	290
Total Lumen	3480
Tj	85
Rated lumens (lm)	
LED Lumen	219.2
Total Lumen	2631
Та	25
·	









Specifications

Material description

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description


Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.





Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300







Optical Accessories

Optical Adaptor

Description	Part ID
Internal optical Adaptor IA	185-7419



Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7581	149






ETC340-GB LED

Surface wash lens

Description	Part ID	C1	
Flood lens IO-360	185-7582	149	



Linear louvre

Description	Part ID	C1	
Linear louvre IL	185-9568	149	



185-7713



ETC340-GB LED

Colour filter

Description	Part ID	
Colour filter IF	on request	

