



#### **Description**

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.


Luminaire installation blockout and sealable junction box included in supply.


ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch <strong><a href="https://vimeo.com/672613058">here.</a></strong>

12.00 kg
symmetric, very narrow beam, sharp cut-off [EES]
LED-12/24W / 700 mA - 3000 K
80
EC
12
27 W
290
3480
85
252.8
3033.1
25







## **Specifications**

## **Material description**

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

#### **Electrical description**


Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

#### **Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.





# **Mounting Accessories**

#### **Installation cover**

Description	Part ID	C1	
Installation cover BE	185-0326	300	



WE-EF LIGHTING Pty Ltd





# **Optical Accessories**

### **Optical Adaptor**

Description	Part ID
Internal optical Adaptor IA	185-7419



### Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7581	149






#### ETC340-GB LED

### **Surface wash lens**

Description	Part ID	C1	
Flood lens IO-360	185-7582	149	



### **Linear louvre**

Description	Part ID	C1	
Linear louvre IL	185-9568	149	



### 185-7714



#### ETC340-GB LED

### **Colour filter**

Description	Part ID	
Colour filter IF	on request	

