ESC340-FS LED





Description

IP67, Class I. IK07. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection.

'No tool' removable gear/reflector tray. Anodised aluminium reflector.

Luminaire requires installation blockout and sealable junction box, which are included in supply.

2700 K option available on request.


IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.


Weight	18.70 kg
Light distribution	symmetric, very narrow beam [EE]
Light source	LED-24/36W / 500 mA - 3000 K
CRI	80
Power supply	EC
LEDs	24
Rated input power	39 W
Nominal Lumen (lm)	
LED Lumen	215
Total Lumen	5160
Тј	85
Rated lumens (lm)	
LED Lumen	150.1
Total Lumen	3602.2
Та	25

185-7721

ESC340-FS LED







Specifications Material description

Body Stainless steel inground section. Die-cast hood made from marine-grade aluminium alloy

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK09

Corrosion resistance 5CE. 5CE+Primer optional

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

Additional information

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details.

Warranty void if installed without proper drainage.

185-7721

ESC340-FS LED



Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300

