



#### **Description**


IP67. Stainless steel construction including PCS hardware. Safety glass lens with opal diffuser, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Complete with cable gland and 0.5 m of flexible PVC-free cable. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. 1-10 V analogue dimming (where applicable) available on request. Luminaire installation blockout and sealable junction box included in supply.


2700 K option available on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch <strong><a href="https://vimeo.com/672613058">here.</a></strong>

Weight	2.80 kg					
Light distribution	symmetric, diffused distribution					
Light source	LED-3/3W / 350 mA - 3000 K					
CRI	80					
Power supply	EC					
LEDs	3					
Rated input power	5.7 W					
Nominal Lumen (lm)						
LED Lumen	155					
Total Lumen	465					
Tj	85					
Rated lumens (lm)						
LED Lumen	45.9					
Total Lumen	137.8					
Та	25					







## **Specifications**

## **Material description**

Body Stainless steel construction

Lens Safety glass lens with opal diffuser, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Corrosion resistance -

### **Electrical description**

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

#### **Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.



# **Mounting Accessories**

#### **Installation cover**

Description	Part ID (	C1
E31	185-9961	125



#### Installation blockout

Description	Part ID	D1	D2	H1	Weight (kg)
BET31	185-8411	119	240	126	0.90

