

Description

Recessed LED wall luminaire.

ADA (American Disabilities Act) Compliant.

IP55. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. 0-10V Dimming comes standard with luminaire.


A pre-installation blockout is available and recommended for mounting in concrete walls; to be ordered separately.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

<u>Weight</u>	7.10 lb				
Light distribution	asymmetric, forward-throw [A60]				
Light source	LED-6/6W / 350 mA - 4000 K				
CRI	80				
Power supply	electronic gear				
LEDs	6				
Rated input power	5.6 W				
Nominal Lumen (lm)					
LED Lumen	170				
Total Lumen	1020				
Tj	85				
Delivered lumens (lm)					
LED Lumen	64.7				
Total Lumen	388.3				
Та	25				





Specifications Material description

Body Luminaire body and lens frame constructed in die cast aluminum.

Lens Tempered glass lens.

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP55
Impact resistance IK08
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter

197-0353



QRI354 LED

Additional information

Lifetime	LED >60,000 h Ta 25°(B10/70) Control gear >50,000 h Ta 25°
----------	--

Listings ETL listed. Suitable for wet locations.



Mounting Accessories

Installation blockout

Description	Part ID	Α	В	C1	C
Installation blockout BQR35-I-RE	197-0129	10.70	10.70	4.92	125

