

Description

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Cable gland with spiral cable bending protection. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Factory-installed circuit board with High Efficiency LEDs. Gimbal mounted, 20° tilt and 355° rotatable.

Suitable for flush installation in concrete or earth. The concrete-pour installation blockout is supplied as standard with luminaire.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

10.30 lb	
symmetric, medium beam [M]	
LED-3/6W / 700 mA - 4000 K	
80	
electronic gear	
3	
7.5 W	
310	
930	
85	
Delivered lumens (lm)	
210.9	
632.8	
25	

ETC120-GB LED ASC





Specifications

Material description

Body Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.

Lens 5/8 in thick Antislip Coating ASC tempered glass lens (Slip Resistance Class R10), max load 5

tonnes

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK10+
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V

Termination Factory sealed termination chamber

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.