

#### **Description**

Anti-Slip ceramic Coating.

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Cable gland with spiral cable bending protection. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. PMMA LED Lens array. Factory-installed circuit board with High Efficiency LEDs. Gimbal mounted, 360° rotatable and 30° tiltable. 'No tool' removable gear/lens tray.

The concrete-pour installation blockout is supplied as standard with luminaire.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black).

+ XXX-XXXX (Accessory 1)

29.90 lb				
symmetric, very narrow beam, 'sharp cut-off' [VNS]				
LED-24/24W / 350 mA - 3000 K				
80				
electronic gear				
24				
26.5 W				
155				
3720				
85				
Delivered lumens (Im)				
128.2				
3076.4				
25				

#### **ETC140-GB LED ASC**





# **Specifications**

## **Material description**

Body Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.

Lens 5/8 in thick Antislip Coating ASC tempered glass lens (Slip Resistance Class R10), max load 5

tonnes

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK10+
Corrosion resistance 5CE

## **Electrical description**

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
<b>-</b>	

Termination Factory sealed termination chamber

#### Additional information

LIFETIME	Ta=25°/40° L90B10 > 90000h
Dimming	0-10V available in request. Must be factory fitted.
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

### **ETC140-GB LED ASC**

# **Optical Accessories**

## **Honeycomb louvre**

Description	Part ID	C1
IW-ETC120_GB_LED Honeycomb	185-2869	2.89
louvre		



IW-ETC140\_GB\_LED 185-2871 5.87





### **ETC140-GB LED ASC**

# **Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	185-9612	2.36

