



Description

Recessed LED wall luminaire.

ADA (American Disabilities Act) Compliant.

IP55. Class I. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. 0-10V Dimming comes standard with luminaire.

A pre-installation blackout is available and recommended for mounting in concrete walls; to be ordered separately.

Specify product with 7 Digit product code – Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)


Weight	16.00 lb
Light distribution	asymmetric, forward-throw [A60]
Light source	14 LED 14W (4000K)
Power supply	electronic gear
LEDs	1
Rated input power	18 W

Delivered lumens (lm)

LED Lumen	548
Total Lumen	548
Ta	25

Nominal Lumen (lm)

LED Lumen	1400
Total Lumen	1400
Tc	25



Specifications

Material description

Body	Luminaire body and lens frame constructed in die cast aluminum.
Lens	Tempered glass lens.
Colors	<div><div></div> RAL9004 Black</div> <div><div></div> RAL9007 Grey Metallic</div> <div><div></div> RAL9016 White</div> <div><div></div> RAL8019 Dark Bronze</div>
Gasket	Silicone rubber gasket
Fasteners	PCS polymer coated stainless steel
Ingress protection	IP55
Impact resistance	IK10
Corrosion resistance	5CE

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
--------------	-----------------------------------------------------------------------------------------

**Additional information**

Ambient Temperature	Ta less than 25 deg C
Listings	ETL listed. Suitable for wet locations.