





### Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens, hinged. Silicone rubber gasket.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Two cable entries. Optional 2200 K version available. To be specified at time of ordering.

Pre-installation blackout is recommended for mounting in cast concrete ceilings, available on request.

Weight	2.10 kg
Light distribution	wallwash
Light source	LED-12/24W / 700 mA - 3000 K
CRI	80
Power supply	EC
LEDs	12
Rated input power	27 W
<b>Nominal Lumen (lm)</b>	
LED Lumen	290
Total Lumen	3480
Tj	85
<b>Rated lumens (lm)</b>	
LED Lumen	200.5
Total Lumen	2405.6
Ta	25



## Specifications

### Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens, hinged
Colours	<div style="display: flex; align-items: center; gap: 10px;"> <div style="width: 20px; height: 15px; background-color: black; margin-bottom: 5px;"></div> RAL9004 Signal black                 <div style="width: 20px; height: 15px; background-color: grey; margin-bottom: 5px; margin-left: 20px;"></div> RAL9007 Grey aluminium                 <div style="width: 20px; height: 15px; background-color: darkgrey; margin-bottom: 5px; margin-left: 20px;"></div> RAL7016 Anthracite grey                 <div style="width: 20px; height: 15px; background-color: white; border: 1px solid black; margin-bottom: 5px; margin-left: 20px;"></div> RAL9016 Traffic white             </div>
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment


### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Mounting Accessories**


**Installation blackout, proud**

Description	Part ID	A	B	C1	C
Installation blackout BDO22-I	134-0797	383	200	209	195



**Installation blackout, flush**


Description	Part ID	A	B	C1	C
Installation blackout BDO22-II	134-1161	383	200	227	195



### Optical Accessories

#### Flood lens

Description	Part ID	C1
Flood lens IO-360	134-1440	105



#### Honeycomb louvre

Description	Part ID	C1
Honeycomb louvre IW	134-1444	105




**DOC220 LED**

**Wallwash lens**

---

Description	Part ID	C1
Wallwash lens IO-20	134-1491	105

---




---

**Linear spread lens**

---

Description	Part ID	C1
Linear spread lens IO-180	134-1381	105

---



**134-1210+134-1491**

**DOC220 LED**

**we-ef**

## **Control**

### **DALI interface**

---

Description	Part ID	C
DALI interface	430-0013	90

---

**WE-EF LIGHTING (Thailand) Co., Ltd.**

57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29

<https://we-ef.com/asia>

Subject to technical changes and errors. - Generated on 23/11/2024