

DAC240 LED




Description

IP65, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Factory installed LED circuit board.


2700 K option available on request.


Weight	7.70 kg
Light distribution	wallwash [A20]
Light source	LED-24/48W / 700 mA - 3000 K
CRI	80
Power supply	EC
LEDs	24
Rated input power	54 W
Nominal Lumen (lm)	
LED Lumen	290
Total Lumen	6960
Tj	85
Rated lumens (lm)	
LED Lumen	202.2
Total Lumen	4851.9
Та	25



we-ef

DAC240 LED





Specifications Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Safety glass lens, hinged			
Colours	RAL9004 Signal black			
	RAL9006 White aluminium			
	RAL9007 Grey aluminium			
	RAL9016 Traffic white			
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)			
Ingress protection	IP65			
Impact resistance	IK07			
Corrosion resistance	5CE+Primer			

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment

Additional information

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

134-1433+134-1492


DAC240 LED

we-ef

Optical Accessories


Surface wash lens


Description	Part ID	C1
IO-360-DAC/DOC240-LED	134-1441	191



Wallwash lens

Description	Part ID	C1
IO-20-WW-DAC/DOC240-LED	134-1492	191






DAC240 LED



Linear spread lens

Description	Part ID	C1
IO-180-DAC/DOC240-LED	134-1382	191





DAC240 LED

we-ef

Control

DALI interface

Description	Part ID	C
DALI interface	430-0013	90