# we-ef

#### **DOC240 LED Stainless Steel**



#### **Description**

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. Two cable entries. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation in non-insulated ceiling. A preinstallation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)


+ XXX-XXXX (Accessory 1)


Weight	8.10 lb
Light distribution	wallwash
Light source	LED-24/48W / 700 mA - 3000 K
CRI	80
Power supply	electronic gear
LEDs	24
Rated input power	54 W
Nominal Lumen (lm)	
LED Lumen	310
Total Lumen	7440
Tj	85
Delivered lumens (lm)	
LED Lumen	216.1
Total Lumen	5186.6
Та	25

#### 134-6300+134-1492









# Specifications Material description

Body Luminaire body constructed in die cast aluminum.

Lens Clear tempered glass lens.

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

# **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

#### **Additional information**

Lifetime LED >60,000 h Ta 25°(L70/B10)
Control gear >50.000 h Ta 25°
Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

#### **WE-EF LIGHTING USA, LLC**

## 134-6300+134-1492



## **DOC240 LED Stainless Steel**

# **Optical Accessories**

# Honeycomb louvre

Description	Part ID	C1
IW-DOC24_LED	134-1445	7.52



## 134-6300+134-1492



## **DOC240 LED Stainless Steel**

## Wallwash lens

Description	Part ID	C1
IO-20-WW-DAC/DOC240-LED	134-1492	7.52



# **Linear spread lens**

ription Part ID	C1
30-DAC/DOC240-LED 134-1382	7.5



#### **WE-EF LIGHTING USA, LLC**