



#### **Description**


IP66, Class I. Class II on request. IK10. Marine-grade, diecast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens. Two cable entries. Factory installed LED circuit board. Integral EC electronic converter.


A pre-installation blockout is available and recommended for mounting in concrete walls. To be ordered separately.

Weight	3.00 kg				
Light distribution	asymmetric, forward-throw [A60]				
Light source	LED-36/8W - 4000 K				
CRI	75				
Power supply	EC				
LEDs	1				
Rated input power	10 W				
Rated lumens (lm)					
LED Lumen	384.8				
Total Lumen	384.8				
Та	25				
Nominal Lumen (lm)					
LED Lumen	1600				
Total Lumen	1600				
Tc	25				









## **Specifications Material description**

Body Marine-grade die-cast aluminium alloy

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone rubber gasket

**Fasteners** PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66 IK10 Impact resistance Corrosion resistance 5CE

### **Electrical description**

220-240V / 50-60 Hz Power supply

Driver / Ballast Integral EC electronic converter

1/2 kV Surge protection

#### **WE-EF LEUCHTEN GmbH**

### 133-0403





## **Additional information**

Lifetime Ta=25° L80B10 > 54000h


Energy efficiency class C (Light source)



# **Mounting Accessories**

### **Installation blockout**

Description	Part ID	Α	В	C1	C
Installation blockout BST27-I	133-0217	447	157	125	130



Installation blockout BST27-II 133-0219 447 157 135 140

