DAC220 LED





Description


IP65, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Factory installed LED circuit board.


2700 K option available on request.

Weight	00 kg	
Light distribution	linear spread, very narrow beam, sharp cut-off [EES]	
Light source	LED-12/24W / 700 mA - 3000 K	
CRI	80	
Power supply	EC	
LEDs	12	
Rated input power	27 W	
Nominal Lumen (lm)		
LED Lumen	290	
Total Lumen	3480	
Tj	85	
Rated lumens (lm)		
LED Lumen	238.8	
Total Lumen	2865.9	
Та	25	









Specifications Material description

Body Marine-grade die-cast aluminium alloy

Colours

RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL9016 Traffic white

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP65
Impact resistance IK07

Corrosion resistance 5CE+Primer

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

Additional information

Lifetime	Ta=40° L90B10 > 90000h		
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement		
	located on www.we-ef.com for further details.		

WE-EF LIGHTING Pty Ltd





Optical Accessories


Linear spread lens

Description	Part ID	C1
0-180-DAC/DOC220-LED	134-1381	105



Surface wash lens

Description	ID C1
IO-360-DAC/DOC220-LED	-1440 105





DAC220 LED

Wallwash lens

Description	Part ID	C1
IO-20-WW-DAC/DOC220-LED	134-1491	105





DAC220 LED

Control

DALI interface

Description	Part ID	С
DALI interface	430-0013	90