



### Description

IP65, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board.

Optional 2200 K version available. To be specified at time of ordering.

|                    |                                      |
|--------------------|--------------------------------------|
| Weight             | 3.00 kg                              |
| Light distribution | linear spread, very narrow beam [EE] |
| Light source       | LED-12/24W / 700 mA - 4000 K         |
| CRI                | 80                                   |
| Power supply       | EC                                   |
| LEDs               | 12                                   |
| Rated input power  | 27 W                                 |

### Nominal Lumen (lm)

|                |      |
|----------------|------|
| LED Lumen      | 310  |
| Total Lumen    | 3720 |
| T <sub>j</sub> | 85   |

### Rated lumens (lm)

|                |        |
|----------------|--------|
| LED Lumen      | 244.5  |
| Total Lumen    | 2933.4 |
| T <sub>a</sub> | 25     |



**134-1430+134-1381**

**DAC220 LED**

**we-ef**

## **Control**

### **DALI interface**

---

| Description    | Part ID  | C  |
|----------------|----------|----|
| DALI interface | 430-0013 | 90 |

---

**Fagerhult Lighting Ltd**

33-34 Dolben Street, SE1 0UQ London, United Kingdom

<https://we-ef.com/uk>

Subject to technical changes and errors. - Generated on 23/11/2024