

Weight

#### **Description**

IP65. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch. Gimbal mounted, 0-30° tiltable and 355° rotatable.

Suitable for installation over recessed junction box. A maximum of one internal optical accessory.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black) + XXX-XXXX (Accessory 1)


Light distribution	symmetric, very narrow beam, 'sharp cut-off' [VNS]
Light source	LED-12/18W / 500 mA - 3000 K
CRI	80
Power supply	electronic gear
LEDs	12
Rated input power	21 W
Nominal Lumen (lm)	
LED Lumen	215
Total Lumen	2580
Тј	85
Delivered lumens (lm)	
LED Lumen	199
Total Lumen	2388.2
Та	25

18.70 lb

# we-ef

#### **DAC240-GB LED**





## **Specifications**

# **Material description**

Body Marine-grade die-cast aluminium alloy

Lens Safety glass lens, hinged

Colors

RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP65
Impact resistance IK07
Corrosion resistance 5CE

## **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

### **Additional information**

Lifetime  $Ta=25^{\circ}/40^{\circ} L90B10 > 90000h$ 

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.



### **DAC240-GB LED**

# **Optical Accessories**

## **Softening Lens**

Description	Part ID	C1	
IO-360-DAC/DOC240-GB-LED	134-1442	3.94	



#### **DAC240-GB LED**

## **Honeycomb louvre**

Description	Part ID	C1
IW-DAC/DOC240-GB LED	134-1449	3.94



## **Linear spread lens**

escription (	Part ID	C1
O-180-DAC/DOC240-GB LED	185-2632	3.94

