





### **Description**

IP66, Class I. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Diffused glass lens. Integral EC electronic converter in thermally-separated compartment. Factory installed LED circuit board. CAD-optimised indirect optics for superior illumination and glare control. Pre-wired post complete with cable connecting box and fuse for mains connection.

Weight	18.00 kg
Light distribution	asymmetric, forward-throw, one- sided
Light source	LED-6/18W / 1050 mA - 4000 K
CRI	80
Power supply	EC
LEDs	6
Rated input power	21 W
Nominal Lumen (lm)	
LED Lumen	450
Total Lumen	2700
Tj	85
Rated lumens (lm)	
LED Lumen	95.3
Total Lumen	571.5
Та	25







# **Specifications Material description**

Body Marine-grade, all-aluminium construction

Lens Diffused glass

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66
Impact resistance IK10

Corrosion resistance 5CE+Primer

### **Electrical description**

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter
Surge protection 10/10kV (SP10) available on request

### Additional information

Lifetime Ta=40° L90B10 > 90000h

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details.


#### **WE-EF LIGHTING Pty Ltd**



# **Mounting Accessories**

### **Planted root**

Description	Part ID	D1	D2	D3	D4	H1	H2	M1	M2	Weight (kg)
Planted root ESV4	300-0464	220	190	102	108	400	350	8	6	4.30









## **Control**

# **Eco Step Dim® Motion**

Description	Part ID
Eco Step Dim® Motion - Linked-	430-0030
Primary	



Eco Step Dim® Motion - Linked-Secondary 430-0031





### **CFY259 LED - 1085 mm**

Description	Part ID
Eco Step Dim® Motion - Stand-Alone	430-0037

