
117-0218 CFY259 LED - 1085 mm




Description

IP66, Class I. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Diffused glass lens. Integral EC electronic converter in thermally-separated compartment. Factory installed LED circuit board. CAD-optimised indirect optics for superior illumination and glare control. Pre-wired post complete with cable connecting box and fuse for mains connection.

Weight	18.00 kg
Light distribution	asymmetric, forward-throw, one- sided
Light source	LED-6/12W / 700 mA - 4000 K
CRI	80
Power supply	EC
LEDs	6
Rated input power	14.5 W
Nominal Lumen (lm)	
LED Lumen	310
Total Lumen	1860
Тј	85
⊺j Rated lumens (lm)	85
	85 65.6
Rated lumens (lm)	





Specifications Material description

Body	Marine-grade, all-aluminium construction
Lens	Diffused glass
Colours	RAL9004 Signal blackRAL9006 White aluminiumRAL9007 Grey aluminium
Gasket	Silicone CCG [®] Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP66
Impact resistance	IK10
Corrosion resistance	5CE+Primer

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Surge protection	10/10kV (SP10) available on request

Additional information

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

47 Tarnard Drive, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499 info.australia@we-ef.com - https://we-ef.com/aus Subject to technical changes and errors. - Generated on 06/09/2025

117-0218

CFY259 LED - 1085 mm

Mounting Accessories

Planted root

Description	Part ID	D1	D2	D3	D4	H1	H2	M1	M2	Weight (kg)
Planted root ESV4	300-0464	220	190	102	108	400	350	8	6	4.30
	M1	10			_					
			D3	D2	D1					
		01								
		0		H2 H	1					
	Ĺ	04								

we-ef

117-0218


CFY259 LED - 1085 mm

we-ef


Control

Eco Step Dim[®] Motion

Description	Part ID
Eco Step Dim [®] Motion - Linked- Primary	430-0030







117-0218

CFY259 LED - 1085 mm

we-ef

Description	Part ID
Eco Step Dim [®] Motion - Stand-Alone	430-0037
_—55	· –]
└ <u>5</u> 7─┘ └_44	