ZFT430 LED





Description

IP66, Class I. Class II on request. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. PMMA main lens. Integral EC electronic converter in thermally separated compartment. DALI. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.


Optional 2200 K version available. To be specified at time of ordering.


Weight	5.50 kg				
Light distribution	rectangular, side throw [R65]				
Light source	LED-9/9W / 350 mA - 3000 K				
CRI	80				
Power supply	EC				
LEDs	9				
Rated input power	11 W				
Nominal Lumen (lm)					
LED Lumen	155				
Total Lumen	1395				
Tj	85				
Rated lumens (lm)					
LED Lumen	131.6				
Total Lumen	1184.7				
Та	25				
·	<u> </u>				

115-1361

ZFT430 LED







Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens PMMA

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK09
Corrosion resistance 5CE

Windage 0.104 m²

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter. DALI

Power factor > 0.9

Surge protection 6/6 kV (optional SP10)

Fagerhult Lighting Ltd

115-1361

ZFT430 LED



Additional information

Lifetime $Ta=25^{\circ} L90B10 > 90000h$

115-1361

ZFT430 LED



Control

Eco Step Dim® Basic

Description	Part ID
Eco Step Dim® Basic LED	430-0001

Eco Step Dim® Advanced

Description	Part ID
Eco Step Dim® Advanced LED	430-0002


ZFT430 LED



Mounting Accessories

Wall and pole brackets RZ

Description	Part ID	C1	D1	D2	D × L1	M1	Weight (kg)
RZO-400 Wall bracket, single	115-1324	277	231	195	76 x 80	12	3.50



RZ2-400 Pole bracket, double	115-1323	258	76 x 100	4.90	
------------------------------	----------	-----	----------	------	--

