



#### Description

IP44, Class I. IK10. Marine-grade aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone rubber gaskets. Prismatic polycarbonate lenses,  $3 \times 120^{\circ}$  offset.

Service door with fused cable connecting box.

Weight	72.00 lb
Light distribution	three sided light output
Light source	LED-FT-37W (3000K)
CRI	80
Power supply	electronic gear
BUG	B1 U3 G1
LEDs	1
Rated input power	42 W
Delivered lumens (lm)	
Delivered lumens (lm) LED Lumen	2546.5
	2546.5 2546.5
LED Lumen	
LED Lumen Total Lumen	2546.5
LED Lumen Total Lumen Ta	2546.5
LED Lumen Total Lumen Ta Nominal Lumen (Im)	2546.5 25





# Specifications Material description

Body Marine-grade, all-aluminium construction

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel hardware

Ingress protection IP44
Impact resistance IK10
Corrosion resistance 5CE

## **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter

Power factor > 0.9

# 116-0207



#### LTP444 LED-FT

### **Additional information**

Lifetime	Ta=25°/40° L70B50 > 50000h
BUG Rating	Please see individual Spec Sheets for classification of Backlight, Uplight and Glare.
Listings	FTI listed Suitable for wet locations

# **Mounting Accessories**

# **Planted root**

Description	Part ID	D1	D2	D3	D4	H1	H2	M1	Weight (lb)
Planted root ESD6	300-0456	13.78	12.2	4.29	5.24	22.83	19.69	.629	22.93

