

#### **Description**


IP44. Class I. IK10. Marine-grade, all aluminum construction. Anodized aluminum reflector. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gaskets. Prismatic polycarbonate lenses. Service door with fused cable connecting box. Factory-installed LED circuit board.


3-Sided Light Distribution [3 x 120° offset].

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black) + XXX-XXXX (Accessory 1)

Weight	72.00 lb
Light distribution	three sided light output
Light source	LED-FT-37W (3000K)
CRI	80
Power supply	electronic gear
BUG	B1 U3 G1
LEDs	1
Rated input power	42 W
Delivered lumens (lm)	
Delivered lumens (lm)  LED Lumen	2546.5
	2546.5 2546.5
LED Lumen	
LED Lumen Total Lumen	2546.5
LED Lumen Total Lumen Ta	2546.5
LED Lumen Total Lumen Ta  Nominal Lumen (Im)	2546.5 25





# Specifications Material description

Body Marine-grade, all-aluminium construction

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Ingress protection IP44
Impact resistance IK10
Corrosion resistance 5CE

### **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter

Power factor > 0.9

Surge protection In-line bracket 10kV Surge Protector

# 116-0208



#### **LSP444 LED-FT**

# **Additional information**

2110411110	Lifetime	Ta=25°/40° L70B50 > 50000h
------------	----------	----------------------------

BUG Rating Please see individual Spec Sheets for classification of Backlight, Uplight and Glare.

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.