

Description


IP44. Class I. IK10. Marine-grade, all aluminum construction. Anodized aluminum reflector. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gaskets. Prismatic polycarbonate lenses. Service door with fused cable connecting box. Factory-installed LED circuit board.


3-Sided Light Distribution [3 x 120° offset].

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black) + XXX-XXXX (Accessory 1)

Weight	37.50 lb
Light distribution	three sided light output
Light source	LED-FT-37W (4000K)
CRI	80
Power supply	electronic gear
BUG	B1 U3 G1
LEDs	1
Rated input power	42 W
Delivered lumens (lm)	
Delivered lumens (Im) LED Lumen	2656.2
	2656.2 2656.2
LED Lumen	
LED Lumen Total Lumen	2656.2
LED Lumen Total Lumen Ta	2656.2
LED Lumen Total Lumen Ta Nominal Lumen (Im)	2656.2 25





Specifications Material description

Body Marine-grade, all-aluminium construction

Lens Prismatic polycarbonate lenses, 3 x 120° offset

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel hardware

Ingress protection IP44
Impact resistance IK10
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter

Power factor > 0.9

Surge protection In-line bracket 10kV Surge Protector

WE-EF LIGHTING USA, LLC

116-0213



LSP434 LED-FT

Additional information

Lifetime	Ta=25°/40° L70B50 > 50000h
BUG Rating	Please see individual Spec Sheets for classification of Backlight, Uplight and Glare.

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.