



Description


IP66. Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. RFC™ Reflection Free Contour main lens. The luminaire is factory-sealed and does not need to be opened during installation.


Integral EC electronic converter. DALI. Factory installed LED circuit board. LED board can be easily removed for upgrading. PMMA OLC® LED lenses for superior illumination and glare control.

Optional 2200 K version available. To be specified at time of ordering.

Weight	9.80 kg	
Light distribution	controlled symmetric distribution [C50]	
Light source	LED-24/48W / 700 mA - 3000 K	
CRI	80	
Power supply	EC	
LEDs	24	
Rated input power	54 W	
Nominal Lumen (lm)		
LED Lumen	290	
Total Lumen	6960	
Tj	85	
Rated lumens (lm)		
LED Lumen	260.5	
Total Lumen	6251.1	
Та	25	







Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens PMMA RFC® Reflection Free Contour technology

Colours RAL9004 Signal black

> RAL9006 White aluminium RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

PCS Polymer Coated Stainless Steel Hardware (unpainted) **Fasteners**

IP66 Ingress protection IK08 Impact resistance

Corrosion resistance 5CE+Primer

 $0.16 \, \text{m}^2$ Windage

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter. DALI

Power factor

In-pole surge protection SP10 device supplied. Please refer to WE-EF installation Surge protection

instructions for details. Use suffix +A for Integral surge protection.

WE-EF LIGHTING Pty Ltd

105-0096





Additional information

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.





Control

Eco Step Dim® Basic

Description	Part ID
Eco Step Dim® Basic LED	430-0001

Eco Step Dim® Advanced

Description	Part ID
Eco Step Dim® Advanced LED	430-0002

R2C Ready to Connect

Description	Part ID	
R2C Ready to Connect (top)	430-0019	