we-ef

ETC330-GB LED



Description

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Optional with Anti-Slip ceramic Coating ASC to DIN 51130 (Trip Classification 10) available on request. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gelimpregnated anti-wicking cable. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. Gimbal mounted, 360° rotatable and 30° tiltable. 'No tool' removable gear/lens tray.

The concrete-pour installation blockout is supplied as standard with luminaire.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black)


+ XXX-XXXX (Accessory 1)

| Weight | 5.50 lb |
|--------------------|------------------------------|
| Light distribution | wallwash |
| Light source | LED-12/12W / 350 mA - 3000 K |
| CRI | 80 |
| Power supply | electronic gear |
| LEDs | 12 |
| Rated input power | 13.9 W |
| Nominal Lumen (lm) | |
| LED Lumen | 155 |
| Total Lumen | 1860 |
| Tj | 85 |
| Rated lumens (lm) | |
| LED Lumen | 108.3 |
| Total Lumen | 1299.6 |
| Та | 25 |

ETC330-GB LED







Specifications

Material description

Body Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.

Lens 5/8" thick clear tempered glass lens. Max. load 5 tonnes.

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK10+
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter
Termination Factory sealed termination chamber

Power factor > 0.9





Additional information

| Lifetime $Ta=25^{\circ}/40^{\circ} L90B10 > 90000h$ | Lifetime | Ta=25°/40° L90B10 > 90000h |
|---|----------|----------------------------|
|---|----------|----------------------------|

Dimming 0-10V available in request. Must be factory fitted.

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.


ETC330-GB LED



Electrical Accessories

Sealable junction box

| Description | Part ID | C1 | M1 | M2 |
|-------------------------------|----------|------|--------|---------------|
| Sealable junction box SJB 130 | 185-1624 | 5.75 | Ø 0.39 | Ø 0.47 - 0.75 |



ETC330-GB LED



Optical Accessories

Linear spread lens

| Description | Part ID | C1 |
|--------------------------|----------|------|
| IO-180 ETC130/330-GB LED | 185-2632 | 3.94 |



Softening Lens






| Description | Part ID | C1 |
|----------------------|----------|------|
| IO-360-ETC130-GB-LED | 185-2866 | 3.86 |



Honeycomb louvre

| Description | Part ID | C1 |
|----------------------|----------|------|
| IW-FTC130/330-GB-LFD | 185-2870 | 3.86 |



ASC Lens





| Description | Part ID | C1 |
|-----------------|----------|------|
| ETC330 ASC Lens | 185-6901 | 6.26 |



185-3095 ETC330-GB LED

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 Phone: +1 724 742 0030

> customersupport.usa@we-ef.com https://we-ef.com/us

Subject to technical changes and errors.

Generated on 10/23/2024

