



#### **Description**


IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens with opal diffuser, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable. Luminaire is factory-sealed and does not need to be opened during installation.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. 1-10 V analogue dimming (where applicable) available on request. Luminaire installation blockout and sealable junction box included in supply.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch <strong><a href="https://vimeo.com/672613058">here.</a></strong>

Weight	2.70 kg
Light distribution	wallwash
Light source	LED-3/6W / 700 mA - 4000 K
CRI	80
Power supply	EC
LEDs	3
Rated input power	7.5 W
Nominal Lumen (lm)	
LED Lumen	310
Total Lumen	930
Tj	85
Rated lumens (lm)	
LED Lumen	163.2
Total Lumen	489.7
Та	25
·	<u> </u>







# **Specifications**

## **Material description**

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Corrosion resistance -

### **Electrical description**

Power supply 230V / 50 Hz


Driver / Ballast Integral EC electronic converter

#### Additional information

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details.

Warranty void if installed without proper drainage.





## **Optical Accessories**

## **Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	185-9612	60



#### **Surface wash lens**

Description	Part ID	C1
Flood lens IO-360	185-9613	60






#### ETC310-FS LED

#### **Wallwash lens**

Description	Part ID	C1	Weight (kg)
Wallwash lens IO-20	185-9950	60	0.01



### **Colour filter**

Description	Part ID	
Colour filter IF	on request	






#### ETC310-FS LED

## **Honeycomb louvre**

Description	Part ID	C1
Honeycomb Louvre IW	185-7181	60



#### **Linear louvre**

Description	Part ID	C1
near louvre IL	185-7134	60





## **Mounting Accessories**

#### **Installation cover**

Description	Part ID	C1		
BE31	185-9961	125		



#### Installation blockout

Desc	ription	Part ID	D1	D2	H1	Weight (kg)
BET3	1	185-8411	119	240	126	0.90

