ETC340-FS LED





Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD-optimised optics for superior illumination and glare control.

Luminaire requires installation blockout and sealable junction box, which are included in supply.

2700 K option available on request.


ASC Anti Slip Coating on request.


IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

Weight	11.00 kg
Light distribution	wallwash
Light source	LED-24/36W / 500 mA - 4000 K
CRI	80
Power supply	EC
LEDs	24
Rated input power	39 W
Nominal Lumen (lm)	
LED Lumen	230
Total Lumen	5520
Tj	85
Rated lumens (lm)	
LED Lumen	155.9
Total Lumen	3741.7
Та	25

ETC340-FS LED







Specifications Material description

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description


Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.





Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300








Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19







Optical Accessories

Surface wash lens

Description	Part ID	C1	
Flood lens IO-360	185-7579	220	



Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7580	220





ETC340-FS LED

Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	185-7589	220

