

Description

RGBW Colour Changer. IP69. IK08. Marine-grade, all-aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Complete with cable gland and 0.5 m of flexible PVC-free cable. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. LED circuit board with WE-EF Colour Boost Technology. DMX interface. For other control interface options to suit specific project requirements, contact WE-EF.

Sealable junction box included in supply.

Pre-installation blockout is recommended for mounting, available on request.


Weight	6.00 kg
Light distribution	symmetric linear, wide beam [LB]
Light source	LED-96/48W - RGBW/4K
CRI	20/80
Power supply	EC
LEDs	96
Rated input power	52 W
Nominal Lumen (lm)	
LED Lumen	51.2
Total Lumen	4920
Tj	85
Rated lumens (lm)	
LED Lumen	33.2
Total Lumen	3191
Та	25

186-0253

ETV130-CC LED







Specifications

Material description

Body Marine-grade, all-aluminium construction

Lens Safety glass lens

Colours

Gasket Silicone rubber gasket

Fasteners PCS hardware

Ingress protection IP69
Impact resistance IK08

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral electronic converter with DMX interface in thermally-separated compartment

Power factor > 0.9

Additional information

Lifatima	Ta=25° L90B10 > 90000h	
Lifetime	Ta=25° L90B10 > 90000h	

186-0253


ETV130-CC LED



Optical Accessories

Honeycomb louvre

Description	Part ID	C1	H1
Honeycomb louvre IW	186-0295	898	30



ETV130-CC LED




Mounting Accessories

Installation blockout, Type I

Description	Part ID	Α	C1	D1	D2	Weight (kg)
BEV130-I-1/927 (1 luminaire)	186-0310	975	160	55	120	4.70





186-0253

ETV130-CC LED



Description	Part ID	Α	C1	D1	D2	Weight (kg)
BEV130-I-3/927 (3 luminaires)	186-0312	2833	160	55	120	13.20



RFV130-I-4/927 (4 luminaires)	186-0313	3762	160	55	120	17 50

