




Description


IP66, Class I. IK07. Marine-grade die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. PMMA-LED lens array. Remote 240 V gear to be ordered separately.


2700 K option available on request.

Weight	2.50 kg			
Light distribution	symmetric, medium beam [M]			
Light source	LED-12/24W - RGBW			
CRI	20/80			
Power supply	EC			
LEDs	12			
Rated input power	27 W			
Nominal Lumen (lm)				
LED Lumen	144.6			
Total Lumen	1735			
Tj	85			
Rated lumens (Im)				
LED Lumen	133.3			
Total Lumen	1599.4			
Та	25			









Specifications Material description

Body Marine-grade die-cast aluminium alloy

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66
Impact resistance IK07

Corrosion resistance 5CE+Primer

WE-EF LIGHTING Pty Ltd





Electrical description

Additional information


Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details.



Optical Accessories


Glare shield

Description	Part ID A	C1
Glare shield ES	146-0156 110	100



Snoot

Description	Part ID A	C1
Snoot ET	146-0397 95,5	126






FLC131 LED #1

Surface wash lens

Description	Part ID	C1
10-360	146-0419	110



Linear spread lens

Description	Part ID	C1	
IO-180-FLC131-LED	146-0418	110	






FLC131 LED #1

Wallwash lens

Description	Part ID	C1
IO-20-WW-FLC131-LED	185-7029	110







Mounting Accessories

Ground spike EF

Description	Part ID	H1	Weight (kg)
Ground spike EF1	310-9102	270	1.20

