

131-9513

VLS410 LED

**we-ef**



#### Description

IP66. Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Safety glass lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Two cable entries.

Luminaire can be mounted for up or down lighting. Optional 2200 K version up to max. 1050mA available. To be specified at time of ordering.

|                           |                                          |
|---------------------------|------------------------------------------|
| Weight                    | 3.30 kg                                  |
| Light distribution        | symmetric, medium beam up and down [M/M] |
| Light source              | LED-2x3/12W / 700 mA - 3000K             |
| CRI                       | 80                                       |
| Power supply              | EC                                       |
| LEDs                      | 6                                        |
| Rated input power         | 15 W                                     |
| <b>Nominal Lumen (lm)</b> |                                          |
| LED Lumen                 | 290                                      |
| Total Lumen               | 1740                                     |
| Tj                        | 85                                       |
| <b>Rated lumens (lm)</b>  |                                          |
| LED Lumen                 | 195.5                                    |
| Total Lumen               | 1173.1                                   |
| Ta                        | 25                                       |

#### WE-EF LIGHTING Pty Ltd

6/13 Downard Street, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499

info.australia@we-ef.com - <https://we-ef.com/aus>

Subject to technical changes and errors. - Generated on 23/11/2024



131-9513

VLS410 LED

**we-ef**

## Mounting Accessories

### Column fitter

| Description | Part ID  | C1 | D1         | H1  | H2  | M1 | Weight (kg) |
|-------------|----------|----|------------|-----|-----|----|-------------|
| CF-410/420  | 131-9140 | 83 | $\geq 140$ | 220 | 100 | 6  | 0.60        |



**131-9513**

**VLS410 LED**

**we-ef**

## **Control**

### **1-10 V analogue dimming interface**

---

| Description                       | Part ID  | C  |
|-----------------------------------|----------|----|
| 1-10 V analogue dimming interface | 430-0011 | 90 |

---

**WE-EF LIGHTING Pty Ltd**

6/13 Downard Street, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499

info.australia@we-ef.com - <https://we-ef.com/aus>

Subject to technical changes and errors. - Generated on 23/11/2024