

FLC240 LED



Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Integral EC electronic converter, thermally separated. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 1-10V, DALI Interface or Eco Step Dim® on request. Maximum one internal optical accessory possible.


Optional 2200 K version up to max. 1050mA available, except version [EES]. To be specified at time of ordering.

|                    |                                |
|--------------------|--------------------------------|
| Weight             | 12.60 kg                       |
| Light distribution | wallwash                       |
| Light source       | LED-24/104W / 1400 mA - 3000 K |
| CRI                | 80                             |
| Power supply       | EC                             |
| LEDs               | 24                             |
| Rated input power  | 106 W                          |

|                    |       |
|--------------------|-------|
| Nominal Lumen (lm) |       |
| LED Lumen          | 550   |
| Total Lumen        | 13200 |
| Tj                 | 85    |

|                   |        |
|-------------------|--------|
| Rated lumens (lm) |        |
| LED Lumen         | 397.8  |
| Total Lumen       | 9548.2 |
| Ta                | 25     |

FLC240 LED



Specifications  
Material description

|                      |                                                                                                                                                                                                                                      |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Body                 | Marine-grade, die-cast aluminium alloy                                                                                                                                                                                               |
| Lens                 | Safety glass lens                                                                                                                                                                                                                    |
| Colours              | <div><div></div> RAL9004 Signal black</div> <div><div></div> RAL9006 White aluminium</div> <div><div></div> RAL9007 Grey aluminium</div> <div><div></div> RAL7016 Anthracite grey</div> <div><div></div> RAL9016 Traffic white</div> |
| Gasket               | Silicone rubber gasket                                                                                                                                                                                                               |
| Fasteners            | PCS Polymer Coated Stainless Steel Hardware                                                                                                                                                                                          |
| Ingress protection   | IP66                                                                                                                                                                                                                                 |
| Impact resistance    | IK07                                                                                                                                                                                                                                 |
| Corrosion resistance | 5CE                                                                                                                                                                                                                                  |
| Windage              | 0.090 m <sup>2</sup>                                                                                                                                                                                                                 |

Electrical description

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| Power supply     | 220-240V / 50-60 Hz                                                             |
| Driver / Ballast | Standard. Optional DALI version available. To be specified at time of ordering. |
| Power factor     | > 0.9                                                                           |
| Surge protection | 6/6 kV (optional SP10)                                                          |

Additional information

|          |                        |
|----------|------------------------|
| Lifetime | Ta=25° L90B10 > 90000h |
|----------|------------------------|

Mounting Accessories

Short post EM

| Description | Part ID  | D1  | D2  | H1  | M1 | Weight (kg) |
|-------------|----------|-----|-----|-----|----|-------------|
| EM1-M16 AL  | 270-9038 | 160 | 130 | 203 | 9  | 2           |



Floodlight mounting bracket TA

| Description                                | Part ID  | A | C1  | D × L1   | Weight (kg) | D × S    |
|--------------------------------------------|----------|---|-----|----------|-------------|----------|
| TA1 Mounting bracket, single* (Ø 76 x 200) | 147-0023 |   | 130 | 76 x 200 | 1.90        | 76 x 200 |




FLC240 LED

| Description                                | Part ID  | A | C1  | D × L1   | Weight (kg) | D × S    |
|--------------------------------------------|----------|---|-----|----------|-------------|----------|
| TA2 Mounting bracket, double* (Ø 76 x 200) | 147-0024 |   | 130 | 76 x 200 | 1.90        | 76 x 200 |



|                                             |          |      |     |          |       |          |
|---------------------------------------------|----------|------|-----|----------|-------|----------|
| TA2-L Mounting bracket, double (Ø 76 x 200) | 147-0105 | ±90° | 420 | 76 x 200 | 16.10 | 76 x 200 |
|---------------------------------------------|----------|------|-----|----------|-------|----------|




FLC240 LED

| Description                               | Part ID  | A    | C1  | D × L1   | Weight (kg) | D × S    |
|-------------------------------------------|----------|------|-----|----------|-------------|----------|
| TA3 Mounting bracket, triple (Ø 89 x 200) | 147-0025 | ±90° | 650 | 89 x 200 | 17.90       | 89 x 200 |



|                                         |          |      |     |          |       |          |
|-----------------------------------------|----------|------|-----|----------|-------|----------|
| TA4 Mounting bracket, quad (Ø 89 x 200) | 147-0099 | ±90° | 650 | 89 x 200 | 20.80 | 89 x 200 |
|-----------------------------------------|----------|------|-----|----------|-------|----------|



FLC240 LED

| Description                                | Part ID  | A | C1  | D × L1    | Weight (kg) | D × S     |
|--------------------------------------------|----------|---|-----|-----------|-------------|-----------|
| TA1 Mounting bracket, single (Ø 108 x 200) | 147-0096 |   | 130 | 108 x 200 | 7.50        | 108 x 200 |



|                                            |          |  |     |           |      |           |
|--------------------------------------------|----------|--|-----|-----------|------|-----------|
| TA2 Mounting bracket, double (Ø 108 x 200) | 147-0097 |  | 130 | 108 x 200 | 7.50 | 108 x 200 |
|--------------------------------------------|----------|--|-----|-----------|------|-----------|



FLC240 LED

| Description                                  | Part ID  | A    | C1  | D × L1    | Weight (kg) | D × S     |
|----------------------------------------------|----------|------|-----|-----------|-------------|-----------|
| TA2-L Mounting bracket, double (Ø 108 x 200) | 147-0148 | ±90° | 420 | 108 x 200 | 20.20       | 108 x 200 |




|                                            |          |      |     |           |       |           |
|--------------------------------------------|----------|------|-----|-----------|-------|-----------|
| TA3 Mounting bracket, triple (Ø 108 x 200) | 147-0098 | ±90° | 650 | 108 x 200 | 24.20 | 108 x 200 |
|--------------------------------------------|----------|------|-----|-----------|-------|-----------|




FLC240 LED

| Description                              | Part ID  | A    | C1  | D × L1    | Weight (kg) | D × S     |
|------------------------------------------|----------|------|-----|-----------|-------------|-----------|
| TA4 Mounting bracket, quad (Ø 108 x 200) | 147-0100 | ±90° | 650 | 108 x 200 | 24.20       | 108 x 200 |




Pole clamp TS

| Description                            | Part ID  | D1    | Weight (kg) | D     |
|----------------------------------------|----------|-------|-------------|-------|
| TS1-2/M12 Pole clamp, single (Ø 76-89) | 147-0543 | 76-89 | 1.40        | 76-89 |




FLC240 LED

| Description                              | Part ID  | D1      | Weight (kg) | D       |
|------------------------------------------|----------|---------|-------------|---------|
| TS1-2/M12 Pole clamp, single (Ø 102-114) | 147-0526 | 102-114 | 1.50        | 102-114 |



|                                          |          |         |      |         |
|------------------------------------------|----------|---------|------|---------|
| TS1-2/M12 Pole clamp, single (Ø 114-133) | 147-0544 | 114-133 | 1.70 | 114-133 |
|------------------------------------------|----------|---------|------|---------|




FLC240 LED

| Description                            | Part ID  | D1    | Weight (kg) | D     |
|----------------------------------------|----------|-------|-------------|-------|
| TS2-2/M12 Pole clamp, double (Ø 76-89) | 147-0545 | 76-89 | 1.40        | 76-89 |




|                                          |          |         |      |         |
|------------------------------------------|----------|---------|------|---------|
| TS2-2/M12 Pole clamp, double (Ø 102-114) | 147-0527 | 102-114 | 1.50 | 102-114 |
|------------------------------------------|----------|---------|------|---------|




FLC240 LED

| Description                              | Part ID  | D1      | Weight (kg) | D       |
|------------------------------------------|----------|---------|-------------|---------|
| TS2-2/M12 Pole clamp, double (Ø 114-133) | 147-0546 | 114-133 | 1.60        | 114-133 |



Planted root


| Description       | Part ID  | D1  | D2  | D3  | D4  | H1  | H2  | M1 | Weight (kg) |
|-------------------|----------|-----|-----|-----|-----|-----|-----|----|-------------|
| Planted root ESV4 | 300-0461 | 145 | 130 | 102 | 108 | 400 | 350 | 8  | 7.05        |




FLC240 LED

Pole clamp PC

| Description                               | Part ID  | D1    | Weight (kg) |
|-------------------------------------------|----------|-------|-------------|
| PC2 76-89/60 Pole clamp, double (Ø 76-89) | 139-2703 | 76-89 | 1.00        |



|                                           |          |       |      |
|-------------------------------------------|----------|-------|------|
| PC1 76-89/60 Pole clamp, single (Ø 76-89) | 139-2702 | 76-89 | 1.00 |
|-------------------------------------------|----------|-------|------|



FLC240 LED

| Description                                      | Part ID  | D1      | Weight (kg) |
|--------------------------------------------------|----------|---------|-------------|
| PC2 102-114/60 Pole clamp, double<br>(Ø 102-114) | 139-2707 | 102-114 | 1.20        |



|                                                  |          |         |      |
|--------------------------------------------------|----------|---------|------|
| PC1 102-114/60 Pole clamp, single<br>(Ø 102-114) | 139-2706 | 102-114 | 1.20 |
|--------------------------------------------------|----------|---------|------|



FLC240 LED

| Description                                      | Part ID  | D1      | Weight (kg) |
|--------------------------------------------------|----------|---------|-------------|
| PC2 114-133/60 Pole clamp, double<br>(Ø 114-133) | 139-2709 | 114-133 | 1.40        |




|                                                  |          |         |      |
|--------------------------------------------------|----------|---------|------|
| PC1 114-133/60 Pole clamp, single<br>(Ø 114-133) | 139-2708 | 114-133 | 1.40 |
|--------------------------------------------------|----------|---------|------|




FLC240 LED

| Description                                | Part ID  | D1     | Weight (kg) |
|--------------------------------------------|----------|--------|-------------|
| PC2 82-109/60 Pole camp, double (Ø 82-109) | 139-2705 | 82-109 | 1.10        |



|                                            |          |        |      |
|--------------------------------------------|----------|--------|------|
| PC1 82-109/60 Pole camp, single (Ø 82-109) | 139-2704 | 82-109 | 1.10 |
|--------------------------------------------|----------|--------|------|



FLC240 LED

Control

Eco Step Dim® Basic

| Description             | Part ID  |
|-------------------------|----------|
| Eco Step Dim® Basic LED | 430-0001 |

Eco Step Dim® Advanced

| Description                | Part ID  |
|----------------------------|----------|
| Eco Step Dim® Advanced LED | 430-0002 |

R2C Ready to Connect

| Description                | Part ID  |
|----------------------------|----------|
| R2C Ready to Connect (top) | 430-0019 |

Optical Accessories


Flood lens

| Description       | Part ID  | C1  |
|-------------------|----------|-----|
| IO-360-FLC240-LED | 139-1856 | 289 |



Honeycomb louvre

| Description         | Part ID  | C1  |
|---------------------|----------|-----|
| Honeycomb Louvre IW | 139-1857 | 279 |



FLC240 LED


Snoot

| Description   | Part ID  | A   | C1  |
|---------------|----------|-----|-----|
| ET-FLC240-LED | 139-1859 | 200 | 346 |



Glare shield


| Description   | Part ID  | A   | C1  |
|---------------|----------|-----|-----|
| ES-FLC240-LED | 139-1858 | 200 | 346 |



FLC240 LED

Wallwash lens

| Description      | Part ID  | Additional information                       | C1  |
|------------------|----------|----------------------------------------------|-----|
| IO-20-FLC240-LED | 139-1854 | for symmetric [M] medium beam luminaire only | 289 |



Linear spread lens

| Description               | Part ID  | C1  |
|---------------------------|----------|-----|
| Linear spread lens IO-180 | 139-1855 | 289 |

