

WE-EF LIGHTING

Installation and Maintenance Instructions

Wall Luminaire Recessed

Reduced Depth (RD)

STL134-RD LED

SVL134-RD LED

STO134-RD LED

STI134-RD LED

Shallow Depth (SD)

STL134-SD LED

SVL134-SD LED

STO134-SD LED

STI134-SD LED



**WARNING :**

This product to be installed by qualified personnel only.

Switch off and isolate the electrical supply during installation.

At no stage is the luminaire to be opened when live. Connections and cables are labelled, before installation ensure the supply matches the luminaire designation.

**ESD Sensitive Device:**

This luminaire contains electrostatic sensitive devices. Do not handle the LED PCB or LED connection leads without suitable ESD prevention methods in place. If in doubt contact WE-EF LIGHTING or an authorised Sales partner. Warranty can be void if the correct handling procedures are not observed.

**Surge Protection:**

For comprehensive protection of a luminaire installation against lightning and electrical surges, it is essential to cover mains supply and data input lines at the distribution board level, by using respective primary (Type 1) and secondary (Type 2) surge arrestors in compliance with EN61643-11/IEC61643-1.

Luminaires designated with the type code '+A' will have an internal Surge Protection Device (SPD) fitted. Street and area luminaries are supplied with an external SPD.

Where an external SPD is supplied, it must be fitted as per the supplied instructions to maintain warranty conditions.

Ensure that all required surge protection measures are in place and activated prior to luminaire installation. Disconnect luminaires before operating high-power devices such as, for example, electrical arc welders.

**Cleaning:**













Apart from cleaning the product's exterior surfaces, no special maintenance work is required. DO NOT use high pressure cleaners on this luminaire

**Notice:**

Unless directed by this installation instruction, the luminaire is to be treated as Factory Sealed with no user serviceable parts. If the luminaire is modified by anybody other than the original manufacturer, the warranty will no longer be valid and shall become the full responsibility of the modifying person/organisation. Claims based on defects attributable to improper installation and/or application, and the consequences thereof, are also excluded.

If the supplied cable of the luminaire is damaged, it must be replaced by WE-EF or a WE-EF authorized agent.

Wall Luminaire Recessed


		STL134-RD		STL134-SD	
					
		SVL134-RD		SVL134-SD	
					
		STO134-RD		STO134-SD	
					
		STI134-RD		STI134-SD	
					

IP66, IK07, Class I, ta = 40°C

Light Source
LED

Accessories:

Installation blackout – Luminaire frame proud of surface.			C
BST13-I	for STL/SVL/STO/STI134	190-9030	130
Installation blackout – Luminaire frame flush with surface.			C
BST13-II	for STL/SVL/STO/STI134	190-9031	145



Installation

The product must be installed and maintained by a suitably qualified professional in compliance with latest building/construction and/or electrical regulations and relevant legislation.

Installation Methods

For concrete or brick walls with recess provided by civil contractor:

- a) BST installation blackout (Fig. I).
- b) Cavity (Fig. II).

For stud walls with provision made by civil or electrical contractor: Simple rectangular opening (Fig. III).




Fig. I




Fig. II





Fig. III

Installation Procedure

- 1) Switch off and isolate mains electrical supply.




- 2) Check that rating shown on luminaire label conforms with mains electrical supply.

we-ef	03/17 IP66 CE
STO134-LED →	220-240V/50-60 Hz
190-XXXX	SOE XXXXXXXX
LED 4000K 5W	item no. XXX


(example)

- 3) Connect cable A with mains supply cable, preferably with sealable junction box (SJB) or other types of waterproof connectors (not supplied by WE-EF):

- a) ON/OFF (L = Phase, N = Neutral, ⊕ = Earthing)
b) 1-10 V/DALI (L = Phase, N = Neutral, ⊕ = Earthing, DA/DA = DALI control line, D-/D+ = 1-10 V control line).



- 4) Set luminaire in position. Secure luminaire by firmly tightening screws J using a Torx T-20 tool, which will drive claws K.



we-ef

www.we-ef.com

WE-EF LEUCHTEN

Germany

Tel +49 5194 909 0

Fax +49 5194 909 299

info.germany@we-ef.com

WE-EF LIGHTING

Thailand

Tel +66 2 738 9610

Fax +66 2 175 2174

info.asiapacific@we-ef.com

WE-EF LUMIERE

France

Tel +33 4 74 99 14 44

Fax +33 4 74 99 14 40

info.france@we-ef.com

WE-EF LIGHTING

Australia

Tel +61 3 8587 0444

Fax +61 3 8587 0499

info.australia@we-ef.com

WE-EF HELVETICA

Switzerland

Tel +41 22 752 49 94

Fax +41 22 752 49 74

info.switzerland@we-ef.com

WE-EF LIGHTING

United States of America

Tel +1 724 742 0030

Fax +1 724 742 0035

info.usa@we-ef.com

WE-EF LIGHTING

United Kingdom


Tel +44 844 880 5346

Fax +44 844 880 5347

info.uk@we-ef.com

T09260W0519 © WE-EF 2019


Technical specifications are
subject to change.



WE-EF LEUCHTEN
Installation and Maintenance
Instructions

Blockout
BST13-I
BST13-II

Blockouts



Installation Blockouts

For exposed concrete walls. To accommodate recessed wall luminaires.

Type I Blockouts

Luminaire faceplate remains proud of wall surface. Actual recessed depth 'C' is kept to a minimum.

Type II Blockouts

For totally flush luminaire installation. Note increased depth 'C'.

Installation blackout – Luminaire frame proud of surface. C

BST13-I	for STL/SVL/STO/STI134	190-9030	130
---------	------------------------	----------	-----

Installation blackout – Luminaire frame flush with surface. C

BST13-II	for STL/SVL/STO/STI134	190-9031	145
----------	------------------------	----------	-----


Installation

The product must be installed and maintained by a suitably qualified professional in compliance with latest building/construction and/or electrical regulations and relevant legislation.

The installation on site must comply with local and/or national health and safety regulations.


Installation Procedure

- 1.1) Determine exact location of mounting frame
A. Secure mounting frame A and mounting grid B to formwork C with nails D (not included).
Where several luminaires are to be installed in one row, pay particular attention to proper alignment.




- 1.2) Pay attention to correct orientation of mounting grid B, depending on using frame type I or II:


Type I




Type II




- 2) Pierce or remove grommet(s) E as required for cables or conduits. Four entry holes allow horizontal or vertical through wiring.




- 3) Pull at least 20 cm of cable(s) F into the block-out and prevent them from slipping out when concrete is poured.



- 4) Slip mounting bucket over mounting grid and secure by pushing the six drive fasteners G through the holes provided.




- 5) Provide adequate reinforcement cage H in order to prevent damage to unit while pouring concrete.



- 6) While pouring concrete, ensure that mounting frame A is not damaged, and that blockout maintains its original shape and remains in its original location.

Follow specifications of DIN1045 regarding pouring of concrete (or those of equivalent inter-national standards). Do not pour concrete from excessive height directly onto block-out.

- 7) After dismantling formwork C, push mounting grid I into the blockout at the center. It'll break and then can be easily removed.



we-ef

www.we-ef.com

WE-EF LEUCHTEN

Germany

Tel +49 5194 909 0

Fax +49 5194 909 299

info.germany@we-ef.com

WE-EF LIGHTING

Thailand

Tel +66 2 738 9610

Fax +66 2 175 2174

info.asiapacific@we-ef.com

WE-EF LUMIERE

France

Tel +33 4 74 99 14 44

Fax +33 4 74 99 14 40

info.france@we-ef.com

WE-EF LIGHTING

Australia

Tel +61 3 8587 0444

Fax +61 3 8587 0499

info.australia@we-ef.com

WE-EF HELVETICA

Switzerland

Tel +41 22 752 49 94

Fax +41 22 752 49 74

info.switzerland@we-ef.com

WE-EF LIGHTING

United States of America

Tel +1 724 742 0030

Fax +1 724 742 0035

info.usa@we-ef.com

WE-EF LIGHTING

United Kingdom

Tel +44 844 880 5346

Fax +44 844 880 5347

info.uk@we-ef.com

T09243W1217 © WE-EF 2017

Technical specifications are
subject to change.

