



**Description**

IP55, Class I. Class II on request. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket.

Polycarbonate main lens. Two cable entries. Integral EC electronic converter.

## Specifications

### Material description

Body	Marine-grade, die-cast aluminium alloy								
Lens	Polycarbonate lens								
Colours	<table><tr><td><b>RAL9004</b> Signal black</td><td><b>RAL9006</b> White aluminium</td><td><b>RAL9016</b> Traffic white</td><td><b>RAL7016</b> Anthracite grey</td></tr><tr><td><b>RAL9007</b> Grey aluminium</td><td></td><td></td><td></td></tr></table>	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey	<b>RAL9007</b> Grey aluminium			
<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey						
<b>RAL9007</b> Grey aluminium									
Gasket	Silicone rubber gasket								
Fasteners	PCS Polymer Coated Stainless Steel hardware								
Corrosion resistance	5CE								

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Polycarbonate lens

### Additional information

**Options**

Light distribution   Colour temperature   Nominal Watt

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
--------------------	---------	--------------	--------------	-------------------	-----