**Description**

IP55, Class I. IK10. Marine-grade die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gaskets. Polycarbonate main lens. CAD-optimised indirect optics for superior illumination and glare control.

Brackets to be ordered separately.

## Specifications

### Material description

Body	Marine-grade, die-cast aluminium alloy		
Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware		
Ingress protection	IP55		
Impact resistance	IK10		
Corrosion resistance	5CE+Primer		

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Surge protection	In-pole surge protection SP10 device supplied. Please refer to WE-EF installation instructions for details. Use suffix +A for Integral surge protection.
Energy efficiency	D (Light source)

### Additional information

Windage	0.12 m <sup>2</sup>
Lifetime	Ta=40° L70B50 > 50000h

**Options**

**Light distribution**



[C60] symmetric distribution

**Colour temperature**

**Nominal Watt**



3000K

17 W

24 W




4000K



2700K

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C60] symmetric distribution	127-1419	LED-1/17W/2700K	2006.8 lm	17 W	80
	127-1260	LED-1/17W/3000K	2099.1 lm	17 W	80
	127-1261	LED-1/17W/4000K	2188 lm	17 W	80
	127-1420	LED-1/24W/2700K	2769.2 lm	24 W	80
	127-1262	LED-1/24W/3000K	2885.4 lm	24 W	80
	127-1263	LED-1/24W/4000K	3008.5 lm	24 W	80