**Description**

IP55, Class I. IK10. Marine-grade die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gaskets. Polycarbonate main lens. CAD-optimised indirect optics for superior illumination and glare control.

Brackets to be ordered separately.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy		
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium
Gasket	Silicone rubber gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware		
Ingress protection	IP55		
Impact resistance	IK10		
Corrosion resistance	5CE+Primer		





Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Surge protection	In-pole surge protection SP10 device supplied. Please refer to WE-EF installation instructions for details. Use suffix +A for Integral surge protection.
Energy efficiency	D (Light source)


Additional information

Windage	0.12 m ²
Lifetime	Ta=40° L70B50 > 50000h

Options

Light distribution	Colour temperature	Nominal Watt
 [C60]	 3000K	17 W 24 W
	 4000K	
	 2700K	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C60]	127-1419	LED-1/17W/2700K	2006.8 lm	17 W	80
	127-1260	LED-1/17W/3000K	2099.1 lm	17 W	80
	127-1261	LED-1/17W/4000K	2188 lm	17 W	80
	127-1420	LED-1/24W/2700K	2769.2 lm	24 W	80
	127-1262	LED-1/24W/3000K	2885.4 lm	24 W	80
	127-1263	LED-1/24W/4000K	3008.5 lm	24 W	80