

### Description

IP66, Class I. Class II on request. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. RFC® Reflection Free Contour main lens. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation. Optional 2200 K version available. To be specified at time of ordering.

Includes cable connector, for cable 9-14 mm. +/- 14° adjustable to compensate for sloping catenary systems.

## Specifications

### Material description

Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey
	<b>RAL9007</b> Grey aluminium			
Ingress protection	IP66			
Impact resistance	IK08			






### Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)



### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options**

Light distribution	Colour temperature	Nominal Watt
 [C50]	 3000K	24 W
		48 W
 [R]	 4000K	
	 2700K	

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	
 [C50]	105-0154	LED-24/24W/3000K	3512.6 lm	24 W	80	
	105-0154-70	LED-24/24W/3000K	4079.2 lm	24 W	70	
	105-0155	LED-24/24W/4000K	3852.5 lm	24 W	80	
	105-0155-70	LED-24/24W/4000K	4305.8 lm	24 W	70	
	105-0247	LED-24/48W/2700K	5822.9 lm	48 W	80	
	105-0247-70	LED-24/48W/2700K	6254.3 lm	48 W	70	
	105-0162	LED-24/48W/3000K	6254.3 lm	48 W	80	
	105-0162-70	LED-24/48W/3000K	7116.9 lm	48 W	70	
	105-0163	LED-24/48W/4000K	6685.6 lm	48 W	80	
	105-0163-70	LED-24/48W/4000K	7548.2 lm	48 W	70	
	 [R]	105-0156	LED-24/24W/3000K	3474.7 lm	24 W	80
		105-0156-70	LED-24/24W/3000K	4035.1 lm	24 W	70
		105-0157	LED-24/24W/4000K	3810.9 lm	24 W	80
105-0157-70		LED-24/24W/4000K	4259.3 lm	24 W	70	
105-0248		LED-24/48W/2700K	5759.9 lm	48 W	80	
105-0248-70		LED-24/48W/2700K	6186.6 lm	48 W	70	
105-0164		LED-24/48W/3000K	6186.6 lm	48 W	80	
105-0164-70		LED-24/48W/3000K	7039.9 lm	48 W	70	
105-0165		LED-24/48W/4000K	6613.3 lm	48 W	80	
105-0165-70		LED-24/48W/4000K	7466.6 lm	48 W	70	