

#### Description

RGBW/RGBA Colour Changer. IP66. Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. RFC® Reflection Free Contour main lens. Integral EC electronic converter in thermally separated compartment. DMX interface. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK08			

### Electrical description

Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options****Light distribution****Colour temperature****Nominal Watt**

[C50] controlled symmetric distribution

3000K+RGBW

95 W





[R] rectangular

4000K+RGBW

RGBA

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[C50] controlled symmetric distribution</p>	105-0315	LED-36/95W/3000K+RGBW	8109.7 lm	95 W	80
	105-0339	LED-36/95W/4000K+RGBW	8109.7 lm	95 W	80
	105-0340	LED-36/95W/RGBA	7225 lm	95 W	60
 <p>[R] rectangular</p>	105-0341	LED-36/95W/3000K+RGBW	7664.6 lm	95 W	80
	105-0342	LED-36/95W/4000K+RGBW	7664.6 lm	95 W	80
	105-0343	LED-36/95W/RGBA	6828.5 lm	95 W	60