**Description**

RGBW/RGBA Colour Changer. IP66. Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG[®] Controlled Compression Gasket. RFC[®] Reflection Free Contour main lens. Integral EC electronic converter in thermally separated compartment. DMX interface. CAD-optimised optics for superior illumination and glare control. OLC[®] One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium
Ingress protection	IP66		
Impact resistance	IK08		
Corrosion resistance	5CE+Primer		

Electrical description

Surge protection	In-pole surge protection SP10 device supplied. Please refer to WE-EF installation instructions for details. Use suffix +A for Integral surge protection.
Energy efficiency	C-D (Light source)



Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution	Colour temperature	Nominal Watt
<input checked="" type="radio"/> [C50]	3000K+RGBW	95 W
<input type="radio"/> [R]	4000K+RGBW	
	RGBA	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C50]	105-0315	LED-36/95W/3000K+RGBW	8109.7 lm	95 W	80
	105-0339	LED-36/95W/4000K+RGBW	8109.7 lm	95 W	80
	105-0340	LED-36/95W/RGBA	7225 lm	95 W	60
 [R]	105-0341	LED-36/95W/3000K+RGBW	7664.6 lm	95 W	80
	105-0342	LED-36/95W/4000K+RGBW	7664.6 lm	95 W	80
	105-0343	LED-36/95W/RGBA	6828.5 lm	95 W	60