

Description

RGBW/RGBA Colour Changer. IP66. Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG[®] Controlled Compression Gasket. RFC[®] Reflection Free Contour main lens. Integral EC electronic converter in thermally separated compartment. DMX interface. CAD-optimised optics for superior illumination and glare control. OLC[®] One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Specifications

Material description

Colours	RAL9004	RAL9006	RAL9007	RAL7016
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	RAL9016			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK08			

Electrical description

Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)



Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution	Colour temperature	Nominal Watt
<input checked="" type="radio"/> [C50]	3000K+RGBW	95 W
<input type="radio"/> [R]	4000K+RGBW	
	RGBA	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C50]	105-0315	LED-36/95W/3000K+RGBW	8109.7 lm	95 W	80
	105-0339	LED-36/95W/4000K+RGBW	8109.7 lm	95 W	80
	105-0340	LED-36/95W/RGBA	7225 lm	95 W	60
 [R]	105-0341	LED-36/95W/3000K+RGBW	7664.6 lm	95 W	80
	105-0342	LED-36/95W/4000K+RGBW	7664.6 lm	95 W	80
	105-0343	LED-36/95W/RGBA	6828.5 lm	95 W	60