

**Description**

Impact-Rated Bollard. IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Diffused safety glass lens. CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board.

Crash rated for small vehicles travelling up to 40mph (SC40), pick-up vehicles travelling up to 40mph (PU40), and medium-duty vehicles travelling up to 30mph (M30).

Pre-wired post complete with cable connecting box and fuse for mains connection.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description



Colors	 Signal black	 Grey aluminium	 Traffic white	 Grey brown
Ingress protection	IP66			
Impact resistance	IK10			

### Electrical description

### Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
----------	----------------------------

**Options**

Light distribution	Color temperature	Nominal Watt
[]	 3000K	24 W
		36 W
	 4000K	18 W
		12 W

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
□	117-0217	LED-6/12W/3000K	368.3 lm	12 W	80
	117-0217	LED-6/12W/3000K	368.3 lm	12 W	80
	117-0217	LED-6/12W/3000K	368.3 lm	12 W	80
	117-0217	LED-6/12W/3000K	368.3 lm	12 W	80
	117-0218	LED-6/12W/4000K	393.7 lm	12 W	80
	117-0218	LED-6/12W/4000K	393.7 lm	12 W	80
	117-0218	LED-6/12W/4000K	393.7 lm	12 W	80
	117-0218	LED-6/12W/4000K	393.7 lm	12 W	80
	117-0215	LED-6/18W/3000K	546.1 lm	18 W	80
	117-0215	LED-6/18W/3000K	546.1 lm	18 W	80
	117-0215	LED-6/18W/3000K	546.1 lm	18 W	80
	117-0215	LED-6/18W/3000K	546.1 lm	18 W	80
	117-0216	LED-6/18W/4000K	571.5 lm	18 W	80
	117-0216	LED-6/18W/4000K	571.5 lm	18 W	80
	117-0216	LED-6/18W/4000K	571.5 lm	18 W	80
	117-0216	LED-6/18W/4000K	571.5 lm	18 W	80
	117-0267	LED-6/24W/3000K	736.6 lm	24 W	80
	117-0267	LED-6/24W/3000K	736.6 lm	24 W	80
	117-0267	LED-6/24W/3000K	736.6 lm	24 W	80
	117-0267	LED-6/24W/3000K	736.6 lm	24 W	80
	117-0268	LED-6/24W/4000K	787.4 lm	24 W	80
	117-0268	LED-6/24W/4000K	787.4 lm	24 W	80
	117-0268	LED-6/24W/4000K	787.4 lm	24 W	80
	117-0268	LED-6/24W/4000K	787.4 lm	24 W	80
	117-0269	LED-6/36W/3000K	1092.3 lm	36 W	80
	117-0269	LED-6/36W/3000K	1092.3 lm	36 W	80
	117-0269	LED-6/36W/3000K	1092.3 lm	36 W	80
	117-0269	LED-6/36W/3000K	1092.3 lm	36 W	80
	117-0270	LED-6/36W/4000K	1143.1 lm	36 W	80
	117-0270	LED-6/36W/4000K	1143.1 lm	36 W	80
	117-0270	LED-6/36W/4000K	1143.1 lm	36 W	80
	117-0270	LED-6/36W/4000K	1143.1 lm	36 W	80

## WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 04/30/2026