

### Description

IP66, Class I. Class II on request. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG<sup>®</sup> Controlled Compression Gasket. Satinised safety glass lens. Integral EC electronic converter in thermally-separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Pre-wired post complete with cable connecting box and fuse for mains connection.

Optional 2200 K version available. To be specified at time of ordering.

Optional Eco Step Dim<sup>®</sup> Motion version available. To be specified at time of ordering.

## Specifications

### Material description

Body	Marine-grade, all-aluminium construction			
Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey
	<b>RAL9007</b> Grey aluminium			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			




### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D (Light source)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options**

Light distribution	Colour temperature	Nominal Watt	
[]		3000K	12 W
			18 W
		4000K	24 W
			36 W
		2700K	

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	117-0328	LED-6/12W/2700K	342.9 lm	12 W	80
	117-0211	LED-6/12W/3000K	368.3 lm	12 W	80
	117-0212	LED-6/12W/4000K	393.7 lm	12 W	80
	117-0329	LED-6/18W/2700K	520.7 lm	18 W	80
	117-0213	LED-6/18W/3000K	546.1 lm	18 W	80
	117-0214	LED-6/18W/4000K	571.5 lm	18 W	80
	117-0330	LED-2x6/24W/2700K	685.8 lm	24 W	80
	117-0273	LED-6/24W/3000K	736.6 lm	24 W	80
	117-0274	LED-6/24W/4000K	787.4 lm	24 W	80
	117-0331	LED-6/36W/2700K	1041.5 lm	36 W	80
	117-0275	LED-6/36W/3000K	1092.3 lm	36 W	80
	117-0276	LED-6/36W/4000K	1143.1 lm	36 W	80