




Description

IP66, Class I, IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Diffused glass lens. Integral EC electronic converter in thermally-separated compartment. Factory installed LED circuit board. CAD-optimised indirect optics for superior illumination and glare control. Pre-wired post complete with cable connecting box and fuse for mains connection.

Specifications

Material description

Body	Marine-grade, all-aluminium construction		
Lens	Diffused glass		
Colours	 RAL9004 Signal black	 RAL9006 White aluminium	 RAL9007 Grey aluminium
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP66		
Impact resistance	IK10		
Corrosion resistance	5CE+Primer		




Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10) available on request
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options

Light distribution	Colour temperature	Nominal Watt
[]	 2700K	18 W
		12 W
	 4000K	24 W
		36 W
	 3000K	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	117-0332	LED-6/12W/2700K	342.9 lm	12 W	80
	117-0217	LED-6/12W/3000K	368.3 lm	12 W	80
	117-0218	LED-6/12W/4000K	393.7 lm	12 W	80
	117-0333	LED-6/18W/2700K	520.7 lm	18 W	80
	117-0215	LED-6/18W/3000K	546.1 lm	18 W	80
	117-0216	LED-6/18W/4000K	571.5 lm	18 W	80
	117-0334	LED-2x6/24W/2700K	685.8 lm	24 W	80
	117-0267	LED-6/24W/3000K	736.6 lm	24 W	80
	117-0268	LED-6/24W/4000K	787.4 lm	24 W	80
	117-0335	LED-6/36W/2700K	1041.5 lm	36 W	80
	117-0269	LED-6/36W/3000K	1092.3 lm	36 W	80
	117-0270	LED-6/36W/4000K	1143.1 lm	36 W	80