

Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Diffused safety glass lens. CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-wired post complete with cable connecting box and fuse for mains connection.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade, all-aluminium construction			
Lens	Diffused glass			
Colors	RAL9004	RAL9016	RAL8019	RAL9007
	Signal black	Traffic white	Grey brown	Grey aluminium
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			




Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	Integral 10kV Surge Protector
Energy efficiency	D (Light source)

Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
[]	 2700K	18 W
		12 W
	 4000K	24 W
		36 W
	 3000K	

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
[]	117-0332	LED-6/12W/2700K	342.9 lm	12 W	80
	117-0217_us	LED-6/12W/3000K	368.3 lm	12 W	80
	117-0218_us	LED-6/12W/4000K	393.7 lm	12 W	80
	117-0333	LED-6/18W/2700K	520.7 lm	18 W	80
	117-0215_us	LED-6/18W/3000K	546.1 lm	18 W	80
	117-0216_us	LED-6/18W/4000K	571.5 lm	18 W	80
	117-0334	LED-2x6/24W/2700K	685.8 lm	24 W	80
	117-0267_us	LED-6/24W/3000K	736.6 lm	24 W	80
	117-0268_us	LED-6/24W/4000K	787.4 lm	24 W	80
	117-0335	LED-6/36W/2700K	1041.5 lm	36 W	80
	117-0269_us	LED-6/36W/3000K	1092.3 lm	36 W	80
	117-0270_us	LED-6/36W/4000K	1143.1 lm	36 W	80