

Description

IP66, Class I. Class II on request. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Satinised safety glass lens. Integral EC electronic converter in thermally-separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Pre-wired post complete with cable connecting box and fuse for mains connection.

Optional 2200 K version available. To be specified at time of ordering.

Optional Eco Step Dim® Motion version available. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, all-aluminium construction			
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey
	RAL9007 Grey aluminium			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			




Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D (Light source)

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution	Colour temperature	Nominal Watt
[]	 2700K	18 W
		12 W
	 4000K	24 W
		36 W
	 3000K	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	117-0332	LED-6/12W/2700K	342.9 lm	12 W	80
	117-0217	LED-6/12W/3000K	368.3 lm	12 W	80
	117-0218	LED-6/12W/4000K	393.7 lm	12 W	80
	117-0333	LED-6/18W/2700K	520.7 lm	18 W	80
	117-0215	LED-6/18W/3000K	546.1 lm	18 W	80
	117-0216	LED-6/18W/4000K	571.5 lm	18 W	80
	117-0334	LED-2x6/24W/2700K	685.8 lm	24 W	80
	117-0267	LED-6/24W/3000K	736.6 lm	24 W	80
	117-0268	LED-6/24W/4000K	787.4 lm	24 W	80
	117-0335	LED-6/36W/2700K	1041.5 lm	36 W	80
	117-0269	LED-6/36W/3000K	1092.3 lm	36 W	80
	117-0270	LED-6/36W/4000K	1143.1 lm	36 W	80