

Description

IP66, Class I. Class II on request. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Integral EC electronic converter in thermally-separated compartment. Factory installed LED circuit board. CAD-optimised optics for superior illumination and glare control. Pre-wired post complete with cable connecting box and service door for mains connection.

Optional Eco Step Dim® Motion version available. To be specified at time of ordering.

Specifications

Material description





Colours	RAL9004	RAL9006	RAL9007	RAL7016
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	RAL9016			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK10			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D-E (Light source)

Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------




Options**Light distribution** [C60] symmetric distribution [C55] controlled symmetric distribution [R50] rectangular**Colour temperature** 3000K 4000K 2700K**Nominal Watt**

12 W

17 W

24 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	
 <p>[C55] controlled symmetric distribution</p>	115-1908	LED-1/12W/2700K	1330.9 lm	12 W	80	
	115-1909	LED-1/12W/3000K	1421 lm	12 W	80	
	115-1910	LED-1/12W/4000K	1497.3 lm	12 W	80	
	115-1911	LED-1/17W/2700K	2034.5 lm	17 W	80	
	115-1912	LED-1/17W/3000K	2128.1 lm	17 W	80	
	115-1913	LED-1/17W/4000K	2218.2 lm	17 W	80	
	115-1914	LED-1/24W/2700K	2807.4 lm	24 W	80	
	115-1915	LED-1/24W/3000K	2925.2 lm	24 W	80	
	115-1916	LED-1/24W/4000K	3050 lm	24 W	80	
 <p>[C60] symmetric distribution</p>	115-1932	LED-1/12W/2700K	1107.8 lm	12 W	80	
	115-1933	LED-1/12W/3000K	1182.8 lm	12 W	80	
	115-1934	LED-1/12W/4000K	1246.2 lm	12 W	80	
	115-1935	LED-1/17W/2700K	1693.4 lm	17 W	80	
	115-1936	LED-1/17W/3000K	1771.3 lm	17 W	80	
	115-1937	LED-1/17W/4000K	1846.3 lm	17 W	80	
	115-1938	LED-1/24W/2700K	2336.7 lm	24 W	80	
	115-1939	LED-1/24W/3000K	2434.8 lm	24 W	80	
	115-1940	LED-1/24W/4000K	2538.6 lm	24 W	80	
	 <p>[R50] rectangular</p>	115-1920	LED-1/12W/2700K	1283.2 lm	12 W	80
		115-1921	LED-1/12W/3000K	1370.1 lm	12 W	80
		115-1922	LED-1/12W/4000K	1443.6 lm	12 W	80
		115-1923	LED-1/17W/2700K	1961.6 lm	17 W	80
115-1924		LED-1/17W/3000K	2051.8 lm	17 W	80	
115-1925		LED-1/17W/4000K	2138.7 lm	17 W	80	
115-1926		LED-1/24W/2700K	2706.8 lm	24 W	80	
115-1927		LED-1/24W/3000K	2820.4 lm	24 W	80	
115-1928		LED-1/24W/4000K	2940.7 lm	24 W	80	