

### Description

IP66, Class I. Class II on request. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Integral EC electronic converter in thermally-separated compartment. Factory installed LED circuit board. CAD-optimised optics for superior illumination and glare control. Pre-wired post complete with cable connecting box and service door for mains connection.

Optional Eco Step Dim® Motion version available. To be specified at time of ordering.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
	Ingress protection	IP66		
Impact resistance	IK10			

### Electrical description


Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D-E (Light source)


### Additional information


Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

## Options

### Light distribution

 [C60] symmetric distribution

 [C55] controlled symmetric distribution

 [R50] rectangular

### Colour temperature

 3000K

 4000K

 2700K




### Nominal Watt

12 W

17 W

24 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C55] controlled symmetric distribution	115-1908	LED-1/12W/2700K	1330.9 lm	12 W	80
	115-1909	LED-1/12W/3000K	1421 lm	12 W	80
	115-1910	LED-1/12W/4000K	1497.3 lm	12 W	80
	115-1911	LED-1/17W/2700K	2034.5 lm	17 W	80
	115-1912	LED-1/17W/3000K	2128.1 lm	17 W	80
	115-1913	LED-1/17W/4000K	2218.2 lm	17 W	80
	115-1914	LED-1/24W/2700K	2807.4 lm	24 W	80
	115-1915	LED-1/24W/3000K	2925.2 lm	24 W	80
 [C60] symmetric distribution	115-1916	LED-1/24W/4000K	3050 lm	24 W	80
	115-1932	LED-1/12W/2700K	1107.8 lm	12 W	80
	115-1933	LED-1/12W/3000K	1182.8 lm	12 W	80
	115-1934	LED-1/12W/4000K	1246.2 lm	12 W	80
	115-1935	LED-1/17W/2700K	1693.4 lm	17 W	80
	115-1936	LED-1/17W/3000K	1771.3 lm	17 W	80
	115-1937	LED-1/17W/4000K	1846.3 lm	17 W	80
	115-1938	LED-1/24W/2700K	2336.7 lm	24 W	80
	115-1939	LED-1/24W/3000K	2434.8 lm	24 W	80
	115-1940	LED-1/24W/4000K	2538.6 lm	24 W	80
 [R50] rectangular	115-1920	LED-1/12W/2700K	1283.2 lm	12 W	80
	115-1921	LED-1/12W/3000K	1370.1 lm	12 W	80
	115-1922	LED-1/12W/4000K	1443.6 lm	12 W	80
	115-1923	LED-1/17W/2700K	1961.6 lm	17 W	80
	115-1924	LED-1/17W/3000K	2051.8 lm	17 W	80
	115-1925	LED-1/17W/4000K	2138.7 lm	17 W	80
	115-1926	LED-1/24W/2700K	2706.8 lm	24 W	80
	115-1927	LED-1/24W/3000K	2820.4 lm	24 W	80
115-1928	LED-1/24W/4000K	2940.7 lm	24 W	80	