

Description

IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-wired post complete with cable connecting box and service door for mains connection.

Suitable for installation in landscaped areas or on concrete foundations.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK10			







Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D-E (Light source)




Additional information

Lifetime	Ta=25°/40° L70B50 > 50000h
----------	----------------------------

Options

Light distribution	Color temperature	Nominal Watt
 [C60] symmetric distribution	 3000K	12 W 17 W 24 W
 [C55] controlled symmetric distribution	 4000K	
 [R50] rectangular	 2700K	

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[C55] controlled symmetric distribution</p>	115-1908	LED-1/12W/2700K	1330.9 lm	12 W	80
	115-1909	LED-1/12W/3000K	1421 lm	12 W	80
	115-1910	LED-1/12W/4000K	1497.3 lm	12 W	80
	115-1911	LED-1/17W/2700K	2034.5 lm	17 W	80
	115-1912	LED-1/17W/3000K	2128.1 lm	17 W	80
	115-1913	LED-1/17W/4000K	2218.2 lm	17 W	80
	115-1914	LED-1/24W/2700K	2807.4 lm	24 W	80
	115-1915	LED-1/24W/3000K	2925.2 lm	24 W	80
	115-1916	LED-1/24W/4000K	3050 lm	24 W	80
 <p>[C60] symmetric distribution</p>	115-1932	LED-1/12W/2700K	1107.8 lm	12 W	80
	115-1933	LED-1/12W/3000K	1182.8 lm	12 W	80
	115-1934	LED-1/12W/4000K	1246.2 lm	12 W	80
	115-1935	LED-1/17W/2700K	1693.4 lm	17 W	80
	115-1936	LED-1/17W/3000K	1771.3 lm	17 W	80
	115-1937	LED-1/17W/4000K	1846.3 lm	17 W	80
	115-1938	LED-1/24W/2700K	2336.7 lm	24 W	80
	115-1939	LED-1/24W/3000K	2434.8 lm	24 W	80
	115-1940	LED-1/24W/4000K	2538.6 lm	24 W	80
	 <p>[R50] rectangular</p>	115-1920	LED-1/12W/2700K	1283.2 lm	12 W
115-1921		LED-1/12W/3000K	1370.1 lm	12 W	80
115-1922		LED-1/12W/4000K	1443.6 lm	12 W	80
115-1923		LED-1/17W/2700K	1961.6 lm	17 W	80
115-1924		LED-1/17W/3000K	2051.8 lm	17 W	80
115-1925		LED-1/17W/4000K	2138.7 lm	17 W	80
115-1926		LED-1/24W/2700K	2706.8 lm	24 W	80
115-1927		LED-1/24W/3000K	2820.4 lm	24 W	80
115-1928		LED-1/24W/4000K	2940.7 lm	24 W	80